Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

A spruce, 5 ins. diam., bears S. 22° W., 7½ lks. dist., mkd. ‡ 82 BT.

Ascead 45 ft. over SE. slope.

- 51.00 Same ridge, bears N. 20° E., curving to N., and S. 20° W.; desc. 94 ft. ever NW. slope, changing to N. slope on ridge.
- 64.00 Leave ridge, bears N. 10° W. and S.; asc. 148 ft. over S. slope, changing to SE. slope.
- 73.335 Point for the N 1/16 sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. dism., 24 ins. in the ground, with bress cap mkd.

N 1/16 S 2 S 1 1960

## from which

- A fir, 4 ins. diam., bears S. 7° E., 612 lks. dist., mkd. N 1/16 S1 BT.
- A fir, 4 ims. diem., bears N. 45° W., 20% lks. dist., mkd. N 1/16 82 BT.

The corner falls slongwide a snag, 20 ins. diem., bears H. 55° E., 6 lks. dist.

Descend 400 ft. along broken E. slope, changing to steep ME. slope.

- 92.20 Top of rock bluff, 100 ft. high, edge bears R. and W.
- 93.81 Intersect the Base Line.

Point for the closing corner of secs. 1 and 2, at proportionate distance in departure; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 22 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 N R 9 W S 36 S 2 S 1 T 1 S R 9 W C C 1959

## from which

An alder, 8 ins. diam., bears S. 37° E., 35 lks. dist., book scribed T18 R9W 81 CC BT.

A fir, 30 ins. diam., bears S. 50° W., 743 lks. dist., mkd. T1S R9W 82 CC BT.

From this point the corner of secs. 35 and 36 only, on the S. bdy. of T. 1 M., R. 9 W., bears S. 87° 17' W., 3.60 chs. dist., previously described.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, hemlock, fir, sprace, alder, and coder, deadened by fire except for the f. 2 mile; undergrowth selecularry, vice maple, devil; club, hucklederry, young aider, and reproduction.

/33