

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

- Chains Land, mountainous.
Soil, rocky clay.
Timber, hemlock, spruce, fir, and alder; undergrowth, salmonberry, vine maple, devil's-club, huckleberry, and reproduction.
-
- From the cor. of secs. 3, 4, 9, and 10.
N. 84° 33' W., bet. secs. 4 and 9.
Ascend 534 ft. over SE. slope, through open logged area.
- 9.70 Gravelled logging road, 15 lks. wide, bears NE. and SW.
- 20.325 Point for the E 1/16 sec. cor. of secs. 4 and 9.
Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mhd.
- E 1/16 $\frac{S 4}{S 9}$
1960
- from which
- A fir, 22 ins. diam., bears N. 7° E., 112 lks. dist.,
mhd. E 1/16 S4 BT.
- A hemlock, 13 ins. diam., bears S. 64½° W., 18 lks. dist.,
mhd. E 1/16 S9 BT.
- The corner falls at W. edge of logged area bearing N. and S.
Ascend 110 ft. over SE. slope, through heavy timber and light undergrowth.
- 24.00 Main ridge dividing Kilchis River and Wilson River drainage, bears NW. and S. 10° E.; desc. 300 ft. over SW. slope, changing to S. slope.
- 37.00 Top of rock bluff, 50 ft. high, bears N. and S.; desc. 140 ft. over steep, rocky W. slope.
- 39.00 Ravine, drains SW.; asc. 30 ft. along S. slope.
- 40.65 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mhd.
- ¼ S 4
¼ S 9
T 1 S R 9 W
1960
- from which
- A fir, 11 ins. diam., bears N. 67½° E., 31 lks. dist.,
mhd. ¼ S4 BT.
- A fir, 16 ins. diam., bears S. 42° W., 91 lks. dist.,
mhd. ¼ S9 BT.
- Descend 70 ft. over SW. slope.
- 42.20 Wet ravine, drains S.; asc. 80 ft. along broken S. slope.
- 46.50 Top of ascent, slopes S.; desc. 150 ft. along S. slope, changing to SW. slope.