

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	
52.00	Head of ravine, drains S.; desc. 50 ft. along S. slope.
58.00	Head of ravine, drains S.; asc. 60 ft. over SE. slope.
60.975	Point for the W 1/16 sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $W \frac{1}{16} \frac{S \frac{4}{8}}{S \frac{9}{9}}$ 1960 </div> from which A fir, 18 ins. diam., bears N. 3½° W., 15 lks. dist., mkd. W 1/16 S4 BT. A fir, 14 ins. diam., bears S. 64° E., 25 lks. dist., mkd. W 1/16 S9 BT. Descend 120 ft. over broken, rocky SW. slope.
69.00	Head of ravine, drains S.; asc. 50 ft. along broken S. slope.
81.30	The cor. of secs. 4, 5, 8, and 9. Land, mountainous. Soil, rocky clay with rock outcroppings. Timber, fir, hemlock, spruce, and alder; undergrowth, huckleberry, salmonberry, devil's-club, vine maple, and reproduction.
<hr/>	
	N. 1° 19' W., bet. secs. 4 and 5. Ascend 34 ft. over rocky SW. slope, through heavy timber and dense undergrowth.
0.80	Spur ridge, bears E. and W.; desc. 740 ft. over steep, rocky, broken NW. slope.
19.76	Branch, 4 lks. wide, course W.; asc. 7 ft. out of bottom.
19.885	Point for the S 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> $S \frac{1}{16}$ $S \frac{5}{5} S \frac{4}{4}$ 1960 </div> from which A fir, 25 ins. diam., bears N. 85° E., 23 lks. dist., mkd. S 1/16 S4 BT. An alder, 22 ins. diam., bears S. 74° W., 48 lks. dist., bark scribed S 1/16 S5 BT. Ascend 430 ft. over steep, rocky SW. slope.
30.70	Spur, slopes S. 70° W.; desc. 140 ft. over steep, rocky NW. slope.
36.50	Branch, 2 lks. wide, course S. 70° W.; asc. 185 ft. over steep, rocky S. slope.