

CHAINS

Page 12.

T4SR8W (cont)

Original Witnesses:

30" fir, N.66°E., 32 Lks.
24" fir, S.63°W., 73 Lks.

I found the original post lying upon the ground in a badly decayed condition. Found 49" snag, S.63°W., 73 Lks with visible marks "1/4". Found the NE BT at its recorded bearing and distance. I set 3x3 fir limb 24" above ground Mkd. 1/4S31 on east side alongside a stone. Corner is on a gentle south slope.

I marked 2 new BTs:

22" fir, N.58°E., 23 Lks. Mkd 1/4S31 BT
15" fir, S.37°E., 8 Lks. Mkd. 3/4S31 BT

Witness: M. Whitmore
by Leonard Whitmore,
Tillamook Co. deputy surveyor
7-13-63

EVALUATION AND RESTORATION OF LAND SECTION CORNERS

T4SR9W

15	14
22	23

Original Monument
Spruce stake and 18x12x8 basalt stone.
No trees were near for witnesses, raised a mound of stone W. of corner 3ft. base.

I found the original spruce stake lying upon the ground with a rock mound at its base. I found a legible "S" on the stake with other marks visible but not legible. A 18x12x8 stone is in place as recorded. No original witnesses were marked. I set 1/2" pine and wired old stake to pipe.

I marked 4 new BTs:

10" fir, S.40°E., 1 1/2ft. Mkd. T4SR9WS23 BT
14" fir, S.16°W., 10 1/2ft Mkd. T4SR9WS22 BT
16" fir, N.22°W., 19.7ft. Mkd. T4SR9WS15 BT
8" fir, N.55°30'E., 15.2ft. Mkd. T4SR9WS14 BT

Corner is west of the Mt. Hebo radar base about 1/4 mile.

Witness: John Lung^dran
Daryl Whitmore
by Leonard Whitmore,
Tillamook Co. deputy surveyor
11-28-60

BOOK 3