

Dependent Resurvey of Portion of Subdivisional Lines of
T. 3 S., R. 10 W.

Chains.	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T3S</td> <td>R10W</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> </table>	T3S	R10W	S 4	S 3	S 9	S10
T3S	R10W						
S 4	S 3						
S 9	S10						
	1933						
	from which						
	A snag, 10 ins. diam., bears N. 74° E., (not N. 67° E.) 23 lks. dist., mkd. S 3 B T. (Old B. T.)						
	A hemlock, 20 ins. diam., bears S. 76° E., (not S. 82° E.) 18 lks. dist., mkd. T 3 S R 10 W S 10 T. (Old B. T.)						
	A snag, 8 ins. diam., bears S. 75° W., (not S. 82° W.) 15 lks. dist., mkd. S 9 B T. (Old B. T.)						
	A hemlock, 14 ins. diam., bears N. 70° W., (not N. 65° W.) 13 lks. dist., mkd. S 4 B T. (Old B. T.)						
	A hemlock, 10 ins. diam., bears S. 31° W., 35 lks. dist., mkd. T 3 S R 10 W S 9 B T. (New B. T.)						
	A hemlock, 20 ins. diam., bears N. 52° E., 34 lks. dist., mkd. T 3 S R 10 W S 3 B T. (New B. T.)						
	Thence						
	N. 3° 30' W., on true line bet. secs. 3 and 4.						
	Asc. 116 ft. over S. slope, through heavy timber and dense undergrowth.						
8.75	Top of rounding spur, slopes SW., desc. 32 ft. over NE. slope.						
11.75	Spring branch, 1 lk. wide, course SW., over rolling land.						
18.11	Asc. 120 ft. over SE. slope.						
21.35	Over rolling land.						
29.34	Desc. 190 ft. over steep NE. slope.						
36.00	Proportionate dist., set an iron post, 3 ft. long, 1 1/2 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>S 4</td> <td>S 3</td> </tr> </table>	S 4	S 3				
S 4	S 3						
	1933						
	from which						
	A hemlock, 16 ins. diam., bears N. 72° E., 76 lks. dist., mkd. 1/4 S 3 B T.						
	A spruce, 50 ins. diam., bears S. 75° W., 56 lks. dist., mkd. 1/4 S 4 B T.						
39.40	Ravine, course E., asc. 24 ft. over SE. slope.						
45.00	Spur, slopes E.						
48.73	Desc. 89 ft. over NE. slope.						