

# County Surveyor's Record, Tillamook County, Oregon

PAGE 2

TOWNSHIP 5 SOUTH, RANGE 8 WEST

C 1/4 CORNER, SECTION 18, T5S, R8W

SET 1 1/4" STAINLESS STEEL PIPE FOR CORNER; ESTABLISHED BY PROPORTIONATE MEASUREMENT BY L. F. CO. BETWEEN COMPUTED EAST 1/4 CORNER AND FOUND C-W 1/16 CORNER.

5

SCRIBED THE FOLLOWING B.T.'S.:

19" FIR BEARS NORTH 36.70 FT. "C 1/4 SEC 18" S. NAIL, L. WASHER, Y. TAG  
8" FIR BEARS S 32° W 7.20 FT. "C 1/4 SEC 18" S. NAIL, L. WASHER, Y. TAG

CORNER IS ON GENTLE SW SLOPE 6.5 FT. SOUTH OF OLD E-W FENCE.

OCTOBER 2, 1967

SCRIBED BY: R. BASS, LFCO.  
WITNESS: R. MCCOLLAM

P.O.T. ON E-W CENTERLINE, SECTION 18, T5S, R8W

SET 1 1/4" X 36" STAINLESS STEEL PIPE.

5

REFERENCED THE FOLLOWING:

5' SNAG BEARS S 88° 03' W 1.94 FT. NO SCRIBE. S. NAIL, L. WASHER, Y. TAG

P.O.T. IS 635.61 FT. S 88° 03' W OF E 1/4 CORNER, SECTION 18, AND 45 FT. WEST OF L.F.CO. RD.

OCTOBER 3, 1967

REFERENCED BY: W. BREWER, LFCO.  
WITNESSES: R. BASS, R. MCCOLLAM

C-E 1/16 CORNER, SECTION 18, T5S, R8W

SET 1/2" IRON PIPE FOR CORNER; ESTABLISHED BY PROPORTIONATE MEASUREMENT BY L.F.CO. BETWEEN COMPUTED EAST 1/4 CORNER AND FOUND C-W 1/16 CORNER.

5

SCRIBED THE FOLLOWING B.T.'S.:

14" FIR BEARS N 35° E 5.10 FT. "CE 1/16" S. NAIL, L. WASHER, Y. TAG  
13" FIR BEARS S 53° E 12.51 FT. "CE 1/16" S. NAIL, L. WASHER, Y. TAG

CORNER IS ON MODERATE SOUTH SLOPE AND IS 16.6 FT. SOUTH OF OLD FENCE.

OCTOBER 5, 1967

SCRIBED BY: R. BASS, LFCO.  
WITNESS: R. MCCOLLAM

S 1/16 CORNER, SECTIONS 18/17, T5S, R8W

SET 1/2" IRON PIPE; ESTABLISHED BY L.F. CO.

5

SCRIBED THE FOLLOWING B.T.'S.:

6" FIR BEARS N 52° W 0.80 FT. "S 1/16 S18" S. NAIL, L. WASHER, Y. TAG  
20" FIR BEARS S 23° E 22.80 FT. "S 1/16 S17" S. NAIL, L. WASHER, Y. TAG

CORNER IS IN FLAT 67 FT. EAST OF N-S FENCE.

VAR. 21° 30'  
OCTOBER 6, 1967

SCRIBED BY: R. BASS, LFCO.  
WITNESSES: R. STEWART, R. MCCOLLAM

BOOK 3

BOOK 3