

feet

County Surveyor's Record, Willamette County, Oregon

- 4,050 Begin descent through heavy salmon berry.
- 4,730 bottom of steep hill, continuing level through Alder and heavy underbrush,
- 4,780 a creek, 10 ft. wide flowing West, continue level through heavy brush across "island."
- 4,950 a creek, 10 ft. wide, flowing West to NW, continue level.
- 5,055 begin ascent through heavy reprod.
- 5,295.37 ~~at level~~ Sec. Cor. East and up on a hill about 130 ft. from gravel road by old mill pond.

Found 1 1/2" pipe in place as per C.S. records.

Replaced pipe with 2x30 in G.I.P. 3 in. brass cap mkd.

T 5 S R 10 W
10/11
 15/14
 1969
 PE 2301
 ORE

from which

- I scribed a 30 in. spruce bears N 49° E, 32.0 ft., mkd. T 5 S R 10 W S 11 BT
- I scribed a 6 in. Hemlock bears S 44° E, 11.5 ft., mkd. T 5 S R 10 W S 14 BT
- I scribed an 8 in. Hemlock bears S 26° W, 6.25 ft., mkd. T 5 S R 10 W S 15 BT
- I scribed a 5 in. Spruce bears N 64° W, 27.5 ft., mkd. T 5 S R 10 W S 10 BT
- I found a 23 in. Hemlock bears S 8° W, 18.5 ft. CS BT, blown down
- I found a 25 in. Hemlock bears S 60° East 35.8 ft, CS BT stump scribing visible.
- I found a 28 in Spruce bears N 69° 30' E 56.5 ft., CS BT Stump scribing visible.

Note: All C.S. B.T.'s were measured to face. The pipe was set at point of corner as per county notes.

Starting at corner of Sections 10, 11, 14, 15, T 5 S, R 10 W and running E along S boundary through dense reprod. of spruce and Hemlock and alder.

- 500 Begin descent
- 850 Creek 8 ft. NW and dense under brush.
- 900 Begin Asc. through scattered timber and dense underbrush,
- 1,308.10 Point for W 1/16 cor. Secs. 11 and 14; N 38° E, 16.6 ft. from old corner stake. set 2x30 in G.I.P., 3 in. Brass Cap, mkd.

W 1/16 11/14
 1969
 PE 2301
 ORE

from which I scribed:

- a 14 in. bark scribed Alder in Alder clump bears N 71 W, 4.5 mkd. W 1/16 S 11 BT
- a 12 in. Spruce bears S 39° W, 24.2 ft., mkd. W 1/16, S 14, BT

Corner sets on gradual slope to the SW

- 1,308= Continue Asc. through scattered timber and underbrush
- 2,616.2 Point for S 1/4 corner Sec. 11, T 5 S, R 10 W 4 ft. south of small creek and 18.5 ft. N 8° W of old 1/4 corner stake set by U.S.F.S.
- BOOK 3 Set 2x30 in G.I.P., 3 in. Brass Cap, Mkd. (297)