


CERTIFIED RECORD OF LAND CORNER MONUMEN

History of original corner establishment:

Corner was established in August of 1882 by the General Land Office.



Description of corner evidence found:

Original 8" hemlock stump for the $\frac{1}{2}$ corner mkd $\frac{1}{2}$ S on NW face from which

A 24" hemlock brs N14W 8.9 ft; original face healed over; newer face with CS $\frac{1}{2}$ scribed; tag good

A 24" hemlock brs N73 $\frac{1}{2}$ W 5.2 ft; face cut out & scribing visible; tag good

Also found a 2 $\frac{1}{2}$ ' stake with 4 sets of notches on one side

Description of monument and accessories established to perpetuate the original location of this corner

Set a 30" iron pipe with brass cap mkd T 3 S R 10 W

$\frac{1}{2}$	$\frac{7}{18}$	W.C.
	18	
	1969	
	650	

as witness to the true corner 4.9 ft due west.
Placed 2 $\frac{1}{2}$ ft stake along side brass cap.
Placed one 6' steel post south of original corner with F.S.
boundary sign facing east. Painted red band around each BT.



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the day of.....; 19....., at..... o'clockm., (signed)
 by
 (COUNTY OFFICIAL) (DEPUTY)