


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in January of 1872 by J. W. Meldrum.



Description of corner evidence found:

Found 4x4x18" much decayed post with faint marks "1/4 S" on west side with old rusted wire laying at base of corner.

No BTs found.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd

T5S R10W

1/4 5 | 4

1970  
650 from which

24" spruce brs. N47 1/2 W 51.7 ft.  
scribed 1/4 Sec. 5 BT - with tag & X

18" alder brs. N20E 24.3 ft.  
scribed 1/4 S4 BT - with tag & X

Placed post beside pipe.

Office of COUNTY SURVEYOR County of TILLAMOOK,  
 State of OREGON, I hereby certify that the within instrument was filed in this office  
 for record on the 15th day of MAY, 1970, at        o'clock        m., (signed)  
[Signature] by CS (DEPUTY)

REGISTERED  
 OREGON  
 LAND SURVEYOR

[Signature]  
 JULY 10, 1964  
 TOM O. McCULLOUGH  
 650

*Rather dubious evidence with no collateral evidence offered to substantiate.*  
 BOOK 3  
 Form R6-7100-57 (9/66)  
 pg. 349