


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by ~~W. P. Wright~~  
J.W. Maldrum  
C



Description of corner evidence found:

Found original 4x4 fir pest mkd "1/4" on south side from which  
18" spruce brs. N82W 86.5 ft  
healed face - with tag  
18" alder brs. S74E 25.0 ft  
bark scribing visible - with tag  
BTs established by M. Whitmore in 1958

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd

T3S R10W

34  
—  
3

1970  
650 from which

14" alder brs. S67W 36.6 ft  
scribed T4S S3 1/4 BT

Set original post alongside corner

Set fence post with sign + 5 ft south facing east

Office of Tillamook County of SURVEYOR  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 13<sup>th</sup> day of May, 1970, at        o'clock        m., (signed)  
[Signature] by        (DEPUTY)  
(COUNTY OFFICIAL)

REGISTERED  
OREGON  
LAND SURVEYOR

[Signature]  
JULY 10, 1964  
TOM O. McCULLOUGH  
650

BOOK 3

368 A OF AB

Survey for Lloyd Sherman 2-24-49  
 Compartment....., Sec....., Twp. 34 S, R. 10 W

Loc. No.	LENGTH	DIAMETER	NET SCALE BY SPECIES				DEFECTS, KIND, AMOUNT
1	Commence at the						2, 3, 34 & 35
2	on the N. E. cor. of T. 4 S. R. 10 W.						
3	within a path 24 in. in diam.						ground original
4	of vegetation that was by						clearing an
5	iron pipe 1 1/2 in. diam.						of long pipe
6	of iron and that part to pipe with						chrom wire
7	chrom wire						
8	One old bearing						4 1/2 lb. diam
9	to N. 40 W 9.6 ft						with scribe marks
0	A line 8 in. diam S 52 W						8 1/2 lbs. mark
1	S. 28 3/4 W lat. on 2 and						3. Var. 21 1/2 SE
2	by M. Whitmore						

M. WHITMORES private notes for a man legal survey (NW not being licensed). However, he was a very reliable and competent man in his field work & scrutiny.

O.P.C. G.S.