

Court Surveyor's Record, Tillamook County, Oregon

238 8

T 3 S., R 9 W.

Witnessed Corners

Mervin Whitmore, U.S. Forest Service

CHAINS

| | |
|-----------|---------|
| Sec. Cor. | 16 15 |
| | 21 22 |

Set a post from which

A 36" fir bears N 28°20' W 130 lks. Large Scar in bark.
 A 30" dead fir snag bears N 74°E 71 lks mkd. T3S R9W S15BT.
 A 30" dead fir snag bears S 70°E 68 lks. not 125 lks as
 recorded in field notes. Mkd. T3S R9W (balance rotted off)
 A 16" fir bears S 70°E 35 feet slope distance mkd. T3S R9W S22BT
 (new BT).

In the presence of Wm. H. Balmer & Joe Bonin. May 23, 1955.

X

c.c. Sec. Cor.

| | |
|---|-------|
| 1 | |
| | 2 1 |

Set a post from which

A dead fir 18" bears S 47°E 14.3 lks. scribing visible (old BT)
 A 6" hemlock dead and fallen bears S 35°W 11 lks under large
 fallen cedar tree. Shows old ax marks but scribing rotted
 off (old BT)
 A 24" fir bears S 59°W 27 feet maked T3S R9W S2BT (new BT)
 A 18" hemlock bears S 15°E 21.3 feet mkd. T3S R9W S1BT (New BT)

In the presence of Martin Chaffee and Ray McKnight. June 14, 1955.

1/2 Sec. Cor.

| | |
|----|----|
| 28 | |
| | 33 |

Set a 3/4" pipe from which

A dead fir snag 41" bears S 45°W 18 lks. distance mkd. 1/2S 33 BT
 (old BT)
 A fir 16" bears N 52°E 13 1/2 feet slope distance mkd. 1/2S 28 BT (new BT)

In the presence of Robert Johnson (B.L.M. forester). Nov. 17, 1954.

Twp. Cor.

| | |
|---------|-----|
| T3S | |
| 36 31 | R9W |
| 1 6 | |
| T4S | |

Set a 1 1/4" pipe 30" above ground for township corner, from which

A dead fir snag 30" bears N 26°E 110 lks. with old scribing
 visible but hardly legible (old BT)

The remains of the other three old BTs are rotted snags and
 stumps; all marks rotted off.

A 14" alder bears N 58°W 5 feet mkd. T3SR9WS36BT (new BT)

A 36" fir bears S 39°E 49 feet mkd. T4SR9WS6BT (new BT)

A 20" fir bears S 70°W 68 feet slope distance mkd. T4SR9WS1BT (new BT)

In the presence of Thomas Nicklaus.

June 16, 1955