

CERTIFIED RECORD OF LAND CORNER MONUMENTS


History of original corner establishment:

Corner was originally set by Sam Caudle in 1880. He set a 4x4 post for the corner & scribed the following BTs:

- A 40" fir brs. S66W 83 lks
- A 60" fir brs. N60W 96 lks
- A 60" fir brs. N10E 140 lks

According to old timers in the area, the Tillamook County Surveyor later set a 12x9x9 stone with an X on top, although no record of such is in the County Surveyor's office.

In 1968 Leonard Whitmore found remnant of a 4x4 post beside a stone with an X notched in same. No scribing was visible on any of * Caudle's BTs. Whitmore set a 1" pipe beside the stone and scribed 4 new BTs (see attached copy)



Description of corner evidence found:


Found a 12x9x9 stone with an X on top and a 1"x36" pipe alongside from which

- A 14" alder brs. N13E 16.0 ft - bark scribed (Whitmore, 1968)
- A 16" alder brs. S54E 35.0 ft - bark scribed (Whitmore, 1968)
- A 20" alder brs. S10W 6.8 ft - bark scribed (Whitmore, 1968)
- A 26" fir brs. N43W 19.5 ft - face partially healed (Whitmore, '68)
- A 40" snag brs. S75W 83 lks - marks rotted away 0216?
- A 60" snag brs. N56W 86 lks - marks rotted away 0216?
- A 60" snag brs. N5E 140 lks - marks rotted away 0216?

** See next page for whitmore's report*

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2"x30" iron pipe with brass cap mkd



Set stone and 1" pipe alongside brass cap

Drove a steel fence post 2 feet west of brass cap with Do Not Destroy sign attached facing north.

Office of COUNTY SURVEYOR County of TILLAMOOK
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 8th day of JULY, 1970, at o'clock m., (signed)
John C. Conline by *Tom O. McCullough*
 (COUNTY OFFICIAL) (DEPUTY)

