

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner has never been established.

DIAGRAM D
Section 6
W 1/16 (Only)

Reference:
Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and brasscap riveted to the top marked:

T 6 S R 10 W

W 1/16
S 6

1973
RLS 942

By proportional measurement.

From which a:

- 30" Hemlock S 70° W 6.7 ft.
mkd "W 1/16 S 6 BT"
- 20" Hemlock S 56° E 26.0 ft.
mkd "W 1/16 S 6 BT"

Witnessed: M. Jackson

Office of County Surveyor County of TILLAMOOK
 State of OREGON I hereby certify that the within instrument was filed in this office
 for record on the 30th day of AUGUST, 1973, at 9:35 o'clock A. m., (signed)
John Cantik
 (COUNTY OFFICIAL) by _____ (DEPUTY)

Set this 25th day of July 1973

BOOK 5 *Edgar L Cook*

232

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Kenneth M. Wightman
OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942