

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM L  
N 1/16 Corner  
Section 6 (Only)

Reference:

Plat dated July 1973 by  
Timberland Services, Inc.  
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S  
R 11 W | R 10 W  
          | N 1/16  
          | S 6

1973

RLS 942

By proportional measurement.

From which a:

- 36" Spruce stump S 51° E 4.4 ft.  
BT tag and paint
- 40" spruce stump S 20° W 22.7 ft.  
BT tag and paint
- 1" iron pipe N 6° 44' 18" E 10.7 ft.
- 1" iron pipe S 6° 44' 18" W 10.5 ft.

This area has recently been logged and there are no suitable trees to use as witness trees.

Witnessed: M. Jackson

Office of COUNTY SURVEYOR County of TUAMOOK  
 State of OREGON I hereby certify that the within instrument was filed in this office  
 for record on the 26th day of AUGUST, 1973, at 9:15 o'clock A.M., (signed)  
*[Signature]* by *[Signature]*  
 (COUNTY OFFICIAL) (DEPUTY)

Set this 26th day of July 1973.

BOOK 5 *Edgar R Cook*

240

Graduate Forest Engineer  
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.  
P.O. Box 668 - Albany, Ore 97321  
Phone: 928-3539

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Kenneth M. Wightman*  
OREGON  
JULY 17, 1970  
KENNETH M. WIGHTMAN II  
942