

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM R
Section 6
C-N-S-N
1/256

Reference:

Plat dated July, 1973, by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I established the location by proportional measurement. The location of the corner falls within the "scour line" of Neskowin Creek. I therefore set a 1" galvanized iron pipe at the corner, from which a:

- 16" Hemlock bears S. 24° E. 29.6 feet
mkd "CNSN 1/256 S 6 BT"
- 10" Hemlock bears South 29.8 feet
mkd "CNSN 1/256 S 6 BT"
- 2 1/2" x 30" galvanized iron pipe on N-S line bears S. 1° 12' 24" E. 15.00 feet
with brasscap marked:

T 6 S R 10 W
S 6
C-N-S-N ↑
1/256 WC
1973
RLS 942

Witnessed: M. Jackson

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 20th day of August, 1973, at 8⁵⁰ o'clock A. m., (signed)
John Cortis by _____
(COUNTY OFFICIAL) (DEPUTY)

Set this 26th day of July, 1973.

246

BOOK 5

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman
OREGON
1973
KENNETH M. WIGHTMAN II
942