


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

Note:

In 1898, the Tillamook County Surveyor set a random 1/4 Section corner in CS 125 (S3-208). Later references call this the C 1/4, but because of the technique used I could not claim it.



Reference:

Plat dated July 1973 by  
Timberland Services, Inc.  
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W  
C 1/4 S 6  
1973  
RLS 942

by proportional measurement.

From which a:

- 20" Hemlock S 64° W 13.4 ft.  
mkd "C 1/4 S 6 BT"
- 20" Hemlock S 31° E 12.1 ft.  
mkd "C 1/4 S 6 BT"

Witnessed: M. Jackson

Office of County Surveyor, County of Tillamook,  
State of OREGON. I hereby certify that the within instrument was filed in this office  
for record on the 20<sup>th</sup> day of AUGUST, 1973, at 8<sup>35</sup> o'clock A.m., (signed)

*Paul Conlin*  
(COUNTY OFFICIAL) by \_\_\_\_\_ (DEPUTY)

Set this 26th day of July 1973.

BOOK 5

*Edgar L. Cook*

250

Graduate Forest Engineer  
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.  
P.O. Box 668 - Albany, Ore. 97321  
Phone: 928-3539

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Kenneth M. Wightman*

OREGON  
JULY 17, 1970  
KENNETH M. WIGHTMAN II  
942