


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally set in 1890, 90.38 chs. West of  $\frac{6\frac{5}{8}}$  and 4.07 chs. North of  $\frac{1}{12}$  7 .

A 14" X 8" X 8" stone was set. A 2 1/2 ft by 4 ft stone mound was raised alongside. No bearing trees were marked.



Reference:

Plat dated July 1973 by Timberland Services, Inc. under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I re-established the location of this corner by proportional measurement and set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S  
R 11 W | S 6  
S 1 | S 7  
R 10 W  
1973  
RLS 942

From which a:

- 42" Spruce S 47° E 22.4 ft. mkd "T 6 S R 10 W S 7 BT"
- 50" Spruce North 123.9 ft. mkd "T 6 S R 10 W S 6 BT"

Witnessed: M. Jackson

Office of COUNTY SURVEYOR County of Tillamook, Oregon  
I hereby certify that the within instrument was filed in this office  
for record on the 20th day of August, 1973, at 8:31 o'clock A.M., (signed)  
J.L. Carlin (COUNTY OFFICIAL) by (DEPUTY)

Set this 27th day of July 1973.

BOOK 5 Edgar L Cook

254

Graduate Forest Engineer  
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.  
P.O. Box 668 - Albany, Ore. 97321  
Phone: 928-3539

REGISTERED PROFESSIONAL LAND SURVEYOR

Kenneth M. Wightman

OREGON  
JULY 17, 1970  
KENNETH M. WIGHTMAN II  
942