


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally set in 1890, 50.38 chains East of  $1 \frac{6}{7}$ . A 4" X 4" X 4' post was set from which a:

- 30" Hemlock S 37° W 30 lks.  
mkd "1/4 S BT"
- 30" Hemlock N 74° E 23 lks.  
mkd "1/4 S BT"



In 1961 M. Whitmore found the original post and both BT's. He marked two new BT's:

- 34" Hemlock S 17° E 32.0 ft.  
mkd "1/4 S 7 BT"
- 34" Hemlock N 88° W 26.5 ft. (30.0 ft. slope distance)  
mkd "1/4 S 6 BT"

Reference:  
Plat dated July 1973 by  
Timberland Services, Inc.  
under my stamp.

Description of corner evidence found:

I found all four BT's. The SW BT is a rotted stump. The NE, SE and NW BT's are stumps with legible scribing.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and brasscap riveted to the top marked:

T 6 S R 10 W

$\frac{S 6}{1/4 S 7}$

1973

RLS 942

There were no suitable trees to mark. I, therefore, set a 1" galvanized iron pipe N 54° 46' 43" W 6.12 ft., a 1" galvanized iron pipe S 54° 46' 43" E 6.96 ft., and marked a 4" Hemlock with an "X" and three nails at base. The 4" Hemlock bears S 28° W 9.2 ft.

Witnessed: E. Tatro

Office of County Surveyor County of Tillamook,  
State of OREGON I hereby certify that the within instrument was filed in this office  
for record on the 20<sup>th</sup> day of AUGUST, 1973, at 9<sup>00</sup> o'clock A.m., (signed)  
[Signature] by \_\_\_\_\_ (DEPUTY)  
(COUNTY OFFICIAL)

Set this 6th day of June, 1973.

BOOK 5 Edgar L Cook  
Graduate Forest Engineer

255

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

Kenneth M. Wightman

OREGON  
JULY 17, 1970  
KENNETH M. WIGHTMAN II  
942