

Beginning at the standard W 1/16 corner, Section 36
heretofore described

Thence N 5° 07' E along the North-South centerline of the
W $\frac{1}{2}$ of Section 36

715.0 Top of hill
1336.8 SW 1/16

Established and monumented by Longview Fibre Company
with a 1 $\frac{1}{4}$ " x 36" stainless steel pipe

From which:

13" Hemlock bears N 19° E 36.92 feet; scribed "SW 1/16
S 36 BT"; screw nail, lead washer, yellow
aluminum section marker plate.


21" Hemlock bears S 6° W 18.01 feet; scribed "SW 1/16
S 36"; screw nail, lead washer, yellow
aluminum section marker plate.

1861.0 Main creek at bend from South, course East

1955.0 Trail, East-West

2673.6 Intersect the East-West centerline of Section 36 at
the CW 1/16

Established and monumented by Longview Fibre Company with
a 1 $\frac{1}{4}$ " x 36" stainless steel pipe with a 2" brass cap affixed
to the top, marked as illustrated:



From which:

17" Hemlock bears N 45° W 12.34 feet; scribed "CW 1/16
S36 BT"; screw nail, lead washer, yellow
aluminum section marker plate.

19" Spruce bears S 86° E 23.60 feet; scribed "CW 1/16
S 36 BT"; screw nail, lead washer, yellow
aluminum section marker plate.

3276.0 Small creek, course N 52° E

3318.0 Creek, 74' wide, course N 45° W