

County Surveyor's Record, Tillamook County, Oregon

10

Feet from which

- An 18" Alder bears N70°W, 55.1 feet to face
Bark scribed 1/4 S33 BT.
- A 42" Alder bears S64°W, 128.6 feet to face
Bark scribed N 1/4 S4 BT 650.

An iron pipe for approximate N 1/4 corner bears West 61 feet. I removed this monument.

Through cutover to North and South

2560.82 This South 1/4 corner to Section 33 which is an OSBF iron post with brass cap as noted on survey filed with the Tillamook County Surveyor by Harold J. Russell. Scribed one additional BT as follows:

- A 24" Alder bears S83°E, 71.3 feet to face
Bark scribed S4 BT.

S89°39'10"E on said Township Line

2904 Branch, 8 feet wide, course N20°W

5061.69 The closing corner to Sections 3 and 4 bears North 4.43 feet, as noted and restored by Harold J. Russell. Found an OSBF iron post with brass cap for corner monument.

5123.14 The original position for the corner to Sections 33, 34, 3, and 4 as established by Henry Meldrum now an angle point on said Township Line. At this point, I set a 2 1/2" x 30" iron post with brass cap marked

T3S R9W

MELDRUM

— 33 — Angle
3 Point

1974 650

from which

- A Fir stump bears N26°E, 62 lks
Face has been cut out and old scribing is visible.
Meldrum called this tree a spruce.
- A Fir stump bears N15°W, 25 lks
Face has been cut out and old scribing is visible.
Meldrum called this tree a spruce.
- An Alder bears S48°E, 57.9 feet (48 lks)
There is an old scar but no visible scribing.
The bearing to this tree is of record but the distance is 8.4 feet long. I used only the two firs for restoration. The original Section 4 BT was not found.

N85°55'55"E on said Township Line

5183.70 The corner to Sections 33 and 34 as originally established by S. Caudle and reestablished by Harold J. Russell in 1967. Such corner is an OSBF iron post with brass cap. The closing corner to Sections 3 and 4 bears N89°45'54"E, 121.86 feet.

Continuing on line between T3 and 4S, R9W,

N89°57'34"E

Enter timber