

County Surveyor's Record, Tillamook County, Oregon

CHAINS

REWITNESSED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

One quarter corner common to Sections 3 and 10, T2N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL

Basalt stone 15" x 13" x 8" (reset on North side of 1½" iron pipe in
place - see below) from which a:

36" Hemlock bears S26°E 52 lks.; now a 48" stump with face rotted out.
30" Hemlock bears N30°E 62 lks.; now a 48" stump with scribe exposed.

RESTORATION by L. W. Amort, August 15, 1952.

1½" x 36" galvanized iron pipe with 3" bronze cap. Placed 1/4 stone on
North side of pipe (in place) from which a:

42" Fir stump bears N71°W 32.5 ft.; now a 42" stump with scribes
1/4 S3 BT RE 2311 visible.
36" Fir stump bears S5°E 78.3 ft.; now a 36" stump with scribes
1/4 S10 BT visible.

REWITNESSED

Var. 21½°E

From above corner monument in mound of rock, a:

6" Fir bears S38°W 4.3 ft. to face; scribed 1/4 S10 BT RS 707.
7" Fir bears N78°W 10.7 ft. to face; scribed 1/4 S3 BT.

Set 4" x 4" x 60" white painted Cedar post 1.0 ft. SE of corner pipe.
Oregon State Forestry Department metal location poster on 6" Fir BT.

Dated December 16, 1974.

Rewitnessed by Steve Ellis under my direction.
Steve Ellis, Compassman

Present and witnessed by Terry Withrow

