


County Surveyor's Record, Tillamook County, Oregon

PAGE 4

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established by Samuel D. Snowden in Sept. 1857 under G.L.O. Contract No. 67. Snowden reports: "Set quarter section post, Var. 20° 30' E, from which a Spruce 32 ins. diam. bears N 10° E 43 lks. dist. A Bearberry 8 ins. diam. bears S80° W 26 lks. dist.



County Survey Book 10, Page 79, reports: "1/4 post on true line bet. sec. 7 & 12, T 2 S, R 9 & 10 W post from which a Fir 60" bears S 00° 45' W 390 lks. present S. J. Miller, A. Biggs, H. Olds, Nov. 3, 1890, V 21°."

In 1915 Reitz Storey and Duffy Inc., an Engineering firm from Seattle Wash., reports on County Survey Map F-19-25: "Set iron pipe in place of corner. 2 B. T. S., 1 down and rotten, original stake."

W. E. Anderson had to find this corner when he set the North and South 1/16 corners between Sections 7 and 12, but I have not found any evidence were he makes a description of this corner other than a calculation tie; Said calculation tie is recorded in County Note Ben.


BOOK 5

Description of corner evidence found:

I found the original 32 inch Spruce bearing tree scribed by Snowden in Sept. 1857. It is now a leaning, very rotten Spruce stump. At S 10° W 28 ft. from the re-constructed upright position of said stump I found flush with the ground a very rusty 1 inch iron pipe as reported being set by Reitz Storey and Duffy Engineers in 1915. I also found the stump remains of the 60 inch Fir reported in Book 10, Page 79.

Description of monument and accessories I established to perpetuate the original location of this corner:

I removed the 1 inch iron pipe and in its place set 1 inch above ground a 2" X 36" concrete filled, galvanized iron pipe with a 3 inch brass cap stamped as shown, from which I scribed three new bearing trees:
 30" fir bears S 27 1/2° E 39.9 ft. to face scribed " 1/4 S7BT "
 6" cherry bears S 3° W 13.3 ft. to face scribed " 1/4 S12BT "
 6" alder bears N 85° W 28.2 ft. to face scribed " 1/4 S12BT "



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Karl F. Foeste

OREGON
JULY 12, 1968
KARL F. FOESTE
0849

BOOK 5

Witnesses:

Recorded in the office of Allen Hofmann County Surveyor, County of Tillamook

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the _____ day of _____

_____ by _____
 (county official) (deputy)

KARL F. FOESTE, Registered Professional Land Surveyor of the State of Oregon