


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *NONE.*




Description of corner evidence found: *NONE.*

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2" x 30" galvanized iron Pipe, flared at bottom and a brass cap riveted on top and extending 4" above the ground.

Set steel Post with Forest Service signs. 2.0ft west of monument.

Stamped disk →



New bearing trees as follows:

12" Fir scribed " W 1/6 510 BT " S 54° 20' W 5.36ft.

12" Fir scribed " W 1/6 53 BT " N 52° W 7.60 ft.

Placed USFS bearing tree signs on each tree breast high facing monument.

Office of COUNTY SURVEYOR County of TILLAMOOK
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 16 day of JUNE, 1971, at 9 o'clock A.m., (signed)
Opal K. C. Co. by _____ (DEPUTY)

REGISTERED
OREGON
LAND SURVEYOR

August C. Giering
JULY 12, 1963
AUGUST C. GIERING
608

BOOK 5

CLARK & GROFF ENGINEERS, INC.
3276 COMMERCIAL STREET S. E.
SALEM, OREGON

Form R6-7100-57 (9/66)

BOOK 5

181