


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was set originally by the GLO in 1879.
They set a post and marked:

- 50" fir S. 63° E., 67 links
- 20" fir N. 46° E., 89 links



(Contract Survey)

Description of corner evidence found:

M. Whitmore in 1958 found the original post and marked 2 new witnesses:

- 14" fir S. 72° E., 56 ft., mkd. "½ S30 BT"
- 9" fir N. 6° W., 24½ ft., mkd. "½ S19 BT"

I found the original post still standing tied to a ½" iron pipe 2 feet above ground. The scribing "½S" was barely visible. The original 20" snag is in place, but the SE BT is gone.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" x 36" Iron pipe with a flared bottom and a brasscap rivited to the top marked:

T.4S. R.9W.

½ $\frac{S\ 19}{S\ 30}$

1971

O.L.S. 816

I tied to the existing BT's and placed new tags and painted red bands on them.

- 18" fir S. 72° E. 55⁷ ft. (scar visible)
- 8" fir N. 6° W. 24⁵ ft. (scar visible)
- 32" fir snag N. 46° E. 60⁴ (58⁷ to face)

I reset the original post tied to the pipe 1 foot East of the corner and set a 6 foot steel post with "Attention" sign 3 feet West.

Office of COUNTY SURVEYOR County of TILLAMOOK
 State of OREGON I hereby certify that the within instrument was filed in this office
 for record on the 8th day of MARCH, 1972 at 4⁵⁵ o'clock P.m., (signed)
John L. Carl by CO. SURVEYOR
 (COUNTY OFFICIAL) (DEPUTY)

Witness:

M. Yinger

Set this 27th day of September 1971.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman

OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942

219