

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM N
N 1/16 Corner
Section 1 (Only)

Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

I found an unrecorded 3/4" iron pipe and one BT marked "T 6 S R 11 W N 1/16 S 1 BT"
Set by LS 784 in 1969.

Description of monument and accessories I established to perpetuate the
original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and brasscap
riveted to the top marked:

T 6 S
R 11 W |
N 1/16 | R 10 W
S 1 |
1973
RLS 942

by proportional measurement.

From which a:

- 20" Spruce S 26° W 44.9 ft.
mkd "T 6 S R 11 W N 1/16 S 1 BT"
- 32" Spruce South 66.3 ft.
mkd "N 1/16 S 1 BT"

The 1/4" pipe bears S 0° 05' 17" E 8.43 ft.

Witnessed: M. Jackson

Office of County Surveyor County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 24 day of AUGUST, 1973, at 9:00 o'clock A. m., (signed)
[Signature] by [Signature]
(COUNTY OFFICIAL) (DEPUTY)

Set this 26th day of July 1973:

BOOK 5 Edgar R Cook

242

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Kenneth M. Wightman
OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942