

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM P
Section 6
C-N-S-NW
1/256

Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W
S 6

C-N-S-NW
1/256

1973
RLS 942

by proportional measurement.

From which a:

- 10" Alder S 34° W 21.6 ft.
mkd "CNSNW 1/256 S 6 BT"
- 10" Alder S 81° W 19.0 ft.
mkd "CNSNW 1/256 S 6 BT"

Witnessed: M. Cook

Office of County Surveyor County of TILLAMOOK
 State of OREGON I hereby certify that the within instrument was filed in this office
 for record on the 30 day of AUGUST, 1973, at 8:30 o'clock A. m., (signed)
Edgar R Cook
 (COUNTY OFFICIAL) by (DEPUTY)

Set this 30th day of July 1973.

BOOK 5 *Edgar R Cook*

244

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman

OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942