

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM W
Section 6
CE 1/16

Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W
E 1/16
C — C
S 6
1973
RLS 942

by proportional measurement.

From which a:

- 30" Spruce S 52° E 9.9 ft.
mkd "CE 1/16 S 6 BT"
- 7" Hemlock S 88° W 13.1 ft.
mkd "CE 1/16 S 6 BT"

Witnessed: M. Jackson

Office of County Surveyor County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 20th day of AUGUST, 1973, at 8⁴⁰ o'clock A.M., (signed)
[Signature] by _____ (DEPUTY)
(COUNTY OFFICIAL)

Set this 26th day of July 1973.

BOOK 5

Edgar R Cook

251

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman

OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942