

# County Surveyor's Record, Tillamook County, Oregon

Feet      Placed the original stone monument on east side of the iron post, and drove the iron pipe flush with ground in mound of rocks.

Continuing on true line between T3 and 4S, R9W

N89°38'26"E

3061      Old dirt road, bears north-south  
 3903.11      Point for the E 1/16 corner to Section 1. I set a 2½" x 30" iron pipe with brass cap marked

T3S   R9W



T4S   R9W


1974      650

from which

- A 26" Fir bears S27°E, 14.8 feet to face  
Scribed E 1/16 S1 BT.
- A 30" Fir bears S84°E, 48.3 feet to face  
Scribed E 1/16 S1 BT 650.

4159      Branch course Northwest  
 5226.52      The corner to T3 and 4S, R8 and 9W, as originally established by Henry Meldrum. At this point, I set a 2½" x 30" iron post with brass cap marked

T3S   R9W



1974      650

from which

- An Alder bears N58°W, 5.0 feet  
Bark scribed T3S R9W S36 BT.
- A Fir bears S39°E, 49.0 feet  
Face healed—scribing not visible.
- A Fir bears S70°W, 68.0 feet (slope distance)  
Face healed—scribing not visible.

Mervin Whitmore scribed the above bearing trees June 16, 1955, in the presence of Thomas Nicklaus, a local landowner. He found all the original BT at that time which were rotted snags and stumps. I found all of these except the northwest BT which is now gone because of a new road.

The corner to the above mentioned Townships and Ranges as established by Caudle bears S12°07'30"W, 221.29 feet. This was originally restored in 1969 by me and the record of same is on file with the Tillamook County Surveyor. I replaced the iron post with a new one marked

*See map 666*