

County Surveyor's Record, Tillamook County, Oregon

12

Feet from which

A 4" Maple bears N29°W, 21.9 feet to face
 Bark scribed S34 BT 650.
 No other good BT's exist within a reasonable distance.

91.08 The closing corner, as established by Douglass, bears South 12.38 feet.

Found the stone with "X" carved on top with an iron pipe alongside.
 At the position for this corner, I set a 2½" x 30" iron pipe with
 brass cap marked

T3S R9W

35

2 | 3

DOUGLASS

T4S R9W

1974 650

from which

A 48" Spruce bears N86°E, 72.0 feet to face
 Scribed CC S2 BT 650.

The corner to Sections 34 and 35 bears N82°17'48"W, 91.91 feet.

Placed the iron pipe and stone alongside the brass cap.

- 895 Enter open pasture
- 1260 Branch, 15 feet wide, course North
- 1985 Branch, 25 feet wide, course N20°W
- 2191 Road bears north-south
- Ascend steep bank
- 2343 Boulder Creek Road
- 2630.79 Position for the South 1/4 corner to Section 35 as originally estab-
 lished by S. Caudle. This point now falls along the north edge of
 the Boulder Creek Road. No trace of the original corner could be
 found. I set a 5/8" iron rod with an aluminum cap stamped

CAUDLE

35
 ———
 2

1974 650

from which

- A 24" Fir bears N57¼°E, 136.0 feet to face
 Scribed S35 BT.
- A 10" Alder bears N51½°E, 61.1 feet to face
 Bark scribed 1/4 S35 BT 650.
- A 25" Fir bears S59½°E, 54.2 feet to face
 Scribed 1/4 S2 BT with "X" above.

A steel fence post bears North 4.8 feet with a yellow metal BT tag
 attached.

See map B-66

~~PLS~~ PLS650