


(21)
 FIELD NOTES FOR RE-ESTABLISHING THE 1/4 COR. TO SEC. 17 & 18, T3N, R9W, W.M. (SEE MY SURVEY OF SEC. 18 & 19 FOR POSITION OF THIS CORNER)




I SET FLUSH A 1 1/2" X 3/8" CONCRETE FILLED, GALV. I. P. WITH 2" BRASS CAP STAMPED AS SHOWN:

FROM WHICH I SCRIBED TWO BEARING TREES:
 A 39" HEMLOCK BEARS N80°W 42.10' TO FACE SCRIBED "1/4 S 18 BT"

A 38" TWIN HEMLOCK BEARS N 45° E 36.30' TO FACE SCRIBED "1/4 S 17 BT"

WITNESSES: S. K. FOESTE, L.S. 849
 12/74
William Hemminger
Allen Hoffmann

(22)
 FIELD NOTES FOR SETTING THE S 1/6 COR. SEC. 17 & 18, T3N, R9W, W.M. (SEE MY SURVEY OF SEC 18 & 19 FOR POSITION OF THIS COR.)



I SET FLUSH A 1 1/2" X 3/8" CONCRETE FILLED, GALV. I. P. WITH 2" BRASS CAP STAMPED AS SHOWN:

FROM WHICH I SCRIBED TWO BEARING TREES:

A 16" HEMLOCK BEARS S83°W 13.70' TO FACE SCRIBED "1/6 S 18 BT"

A 32" HEMLOCK BEARS N 14° E 62.3' TO FACE SCRIBED "S 1/6 S 17 BT"

WITNESSES: K. FOESTE, L.S. 849
 12/74
William Hemminger
Allen Hoffmann

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
 JULY 12, 1968
 KARL F. FOESTE
 0849