

County Surveyor's Record, Tillamook County, Oregon

CHAINS

D-150

GOVERNMENT CORNER RESTORATION

POLK COUNTY, OREGON

At the closing corner to Sections 13 and 24 in Township 6 South, Range 9 West of the Willamette Meridian, said corner also being on the West boundary of Township 6 South, Range 8 West of the Willamette Meridian, I find two FIR stumps agreeing well with the GLO records of 1887 and from said stumps I re-established the corner point at which I set a 1 1/2" X 30" Iron Pipe with 2" Polk County Brass Cap marked: " T.6S., R.9W., S 13, S 24, S 18, R.8W. 1977". The old stumps I found are as follows:

60" (60") FIR STUMP, N.35°W., 9.9 feet to face, scribes "S 13 BT" visible. 55" (50") FIR STUMP, S.20°W., 11.2 feet to face, scribes "SR S 2 BT" visible. I marked the following new trees: 8" D. FIR, N.28 1/2°W., 16.0 feet to face, 16.3 feet to center, marked: "T.6S., R.9W., S 13 BT". 10" HEM., S.85 1/2°E., 32.4 feet to face, 32.9 feet to center, Marked: "T.6S., R.8W., S 18 BT". 13" D. FIR, S.47°W., 16.6 feet to face, 17.1 feet to center, Marked: "T.6S., R.9W., S 24 BT". The corner to Sections 18 and 19 in Township 6 South, Range 8 West bears S. 103.61 feet (Record 100.32 feet).

MAG. VAR. 20°E.

7-11-77

Witness: R. Schulson
D. Shackelford

659	652
Till 1300	12 Polk
Lin. 24	19 Polk
cc	

REGISTERED
PROFESSIONAL
LAND SURVEYOR

C. Ralph Blanchard
OREGON
JULY 22, 1947
C. RALPH BLANCHARD
786

BOOK 6