

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 40 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ W., 244 lks.
dist., with healed blaze.

and bearing trees mkd. by Mervin Whitmore, Deputy County
Surveyor, in 1961

A fir, 29 ins. diam., bears N. 20° W., 11 lks.
dist., with healed blaze.

A fir, 19 ins. diam., bears S. 38° W., 34 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

T 4 S R 9 W

$\frac{1}{4}$ $\frac{S 8}{S 17}$

1978

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, perpetuated and record-
ed by Mervin Whitmore, Deputy County Surveyor, in 1961,
monumented with a fir post, 4 ins. square, firmly set, in
a mound of stone, 2 ft. base, 1 ft. high, projecting 20
ins. above ground, mkd. 4S on S. and $\frac{1}{4}$ S on N. faces,
from which the remains of the original bearing trees:

An alder, 22 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E., $35\frac{1}{2}$
lks. dist., no marks visible on open and decayed
blaze.

An alder, 19 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ W., $47\frac{1}{2}$ lks.
dist., with healed blaze.

and bearing trees mkd. by Whitmore

A fir, 19 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ E., 99 lks.
dist., with healed blaze.

A fir, 12 ins. diam., bears N. 15° W., 83 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground, in a mound of stone, 3 ft. base, to top,
with brass cap mkd.

T 4 S R 9 W

$\frac{1}{4}$
S 7 | S 8

1978

Reset fir post and set a 5 ft. steel fence post
alongside iron post.