

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

An alder, 28 ins. diam., bears N. 13° 40' W., 118 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4	S R	9 W
S 10		S 11
S 15		S 14
1978		

from which a new bearing tree

An alder, 16 ins. diam., bears S. 8½° E., 44 lks. dist., mkd. T4S R9W S14 BT on bark.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 2, 3, 10, and 11, determined at record bearing and distance from the original bearing trees:

An alder, 12 ins. diam., bears N. 38° E., 49 lks. dist., with healed blaze.

An alder, 28 ins. diam., bears S. 80° 50' E., 26 lks. dist., with healed blaze.

An alder, 24 ins. diam., bears S. 85½° W., 51 lks. dist., with healed blaze.

An alder, 18 ins. diam., bears N. 53° W., 57 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4	S R	9 W
S 3		S 2
S 10		S 11
1978		

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 2 and 11, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1969, monumented with an unmarked fir post, 4 ins. square, firmly set, projecting 24 ins. above ground, from which an original bearing tree:

An alder, 18 ins. diam., bears S. 9½° E., 42 lks. dist., with scribe mark 1 visible on opened blaze.

and bearing trees mkd. by Whitmore

A fir, 48 ins. diam., bears N. 2½° W., 23 lks. dist., with healed blaze.

A fir, 52 ins. diam., bears S. 60° W., 123 lks. dist., with healed blaze.