

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 27 ins. diam., bears S. 32° W., 16 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, spruce)

A root hole, bears N. 80½° W., 26 lks. dist., with a down fir alongside, 8 ins. diam., no marks visible. (Record, spruce)

and a bearing tree mkd. by Leonard Whitmore, Deputy County Surveyor, in 1973

A fir, 40 ins. diam., bears N. 14° E., 48 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 6\ S\ R\ 10\ W \\ \quad S\ 7\ | S\ 8 \\ \quad S\ 18\ | S\ 17 \\ \quad \quad 1979 \end{array}$$

from which new bearing trees

A fir, 23 ins. diam., bears S. 34° W., 65 lks. dist., mkd. T6S R10W S18 BT.

A fir, 42 ins. diam., bears N. 88° W., 51 lks. dist., mkd. T6S R10W S7 BT.

The ¼ sec. cor. of secs. 7 and 18, determined at record distance from the original bearing trees:

A hemlock, 26 ins. diam., bears N. 22° E., 45 lks. dist., with scribe mark S visible on opened blaze.

An alder, 21 ins. diam., bears S. 26½° E., 25 lks. dist., with scribe marks ¼ S BT visible on bark. (Record, S. 31° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 6\ S\ R\ 10\ W \\ \quad \quad \frac{1}{4} \quad S\ 7 \\ \quad \quad \quad S\ 18 \\ \quad \quad \quad 1979 \end{array}$$

from which new bearing trees

A hemlock, 22 ins. diam., bears N. 1° W., 48½ lks. dist., mkd. ¼ S7 BT.

A hemlock, 12 ins. diam., bears S. 22½° W., 46 lks. dist., mkd. ¼ S18 BT.

The ¼ sec. cor. of secs. 7 and 8, determined at record distance from the original bearing trees:

A spruce, 25 ins. diam., bears S. 38° E., 13 lks. dist., with healed blaze. (Record, hemlock)