

Remonumentation of Certain Original Corner Points,  
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 15 ins. diam., bears S.  $75\frac{1}{2}^{\circ}$  E., 40 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, S.  $78\frac{1}{2}^{\circ}$  E.)

A spruce, 60 ins. diam., bears N.  $62^{\circ}$  W., 64 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
S 8   S 9
S 17   S 16
1979

from which new bearing trees

A spruce, 25 ins. diam., bears N.  $69^{\circ}$  E., 90 lks. dist., mkd. T6S R10W S9 BT.

A spruce, 32 ins. diam., bears S.  $56\frac{1}{2}^{\circ}$  E.,  $65\frac{1}{2}$  lks. dist., mkd. T6S R10W S16 BT.

No suitable tree available in sec. 17.

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1973, monumented with an iron rod,  $\frac{1}{2}$  in. diam., firmly set, projecting 20 ins. above ground, from which the only remaining original bearing tree:

A fir, 47 ins. diam., bears N.  $1^{\circ}$  E., 76 lks. dist., with scribe mark S visible on opened blaze. (Record, spruce)

and a bearing tree mkd. by Whitmore

A spruce, 17 ins. diam., bears N.  $49\frac{1}{2}^{\circ}$  W.,  $29\frac{1}{2}$  lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
$\frac{1}{4}$
S 18   S 17
1979

from which a new bearing tree

A spruce, 13 ins. diam., bears S.  $72^{\circ}$  E., 64 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Reset iron rod alongside iron post.

The cor. of secs. 7, 8, 17, and 18, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 49 ins. diam., bears S.  $13^{\circ}$  E., 47 lks. dist., with healed blaze. (Record, spruce)