

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 50 ins. diam., bears N. 10° W., 43 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
 $\frac{1}{4}$ $\frac{S 22}{S 27}$
1979

from which new bearing trees

An alder, 16 ins. diam., bears N. $16\frac{1}{2}^\circ$ W., 77 lks. dist., mkd. $\frac{1}{4}$ S22 BT on bark.

A fir, 4 ins. diam., bears S. 55° E., 43 lks. dist., mkd. X BT.

(Remonumenting a corner established by Samuel G. Caudle, U. S. Deputy Surveyor, in 1880, redescribed by Jefferson D. Fenton, U. S. Deputy Surveyor, in 1885, and remonumented by Morris Wygant, U. S. Deputy Surveyor, in 1908)

The $\frac{1}{4}$ sec. cor. of sec. 15 only, on the S. bdy. of the sec., perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1971, monumented with a stone, 13 x 7 x 5 ins., firmly set 6 ins. in the ground, mkd. X on top, and $\frac{1}{4}$ on N. face, from which the remains of an original bearing tree:

A hemlock snag, 28 ins. diam., bears South, 10 lks. dist., with scribe marks $\frac{1}{4}$ visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
 $\frac{1}{4}$ S 15
1979

from which new bearing trees

A hemlock, 32 ins. diam., bears N. $71\frac{1}{2}^\circ$ E., 131 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

A hemlock, 17 ins. diam., bears N. 31° W., 9 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Deposit corner stone alongside iron post.