

Page 10  
CONTAINS

1/4 SECTION 31 T4N R10W WM

ORIGINAL: 1892 - 1/4 Corner 31 & 6

Set post 4' long, 4" square, 24" in ground, for 1/4 section corner and marked "1/4 S" on north face from which a:

- 12" hemlock bears N22°W, 47 links, marked "1/4 SBT."
- 10" hemlock bears S44°E, 21 links, marked "1/4 SBT."

STATE PARKS CREW FOUND:

- 2 1/2" iron pipe set by Crown Zellerbach with 3" cap marked "T4N R10W 1/4 31 1973 RS954."
- 4"x4" white post 3.0' high, 1.5' east of iron pipe.
- 18" hemlock S20°W, 29.4' to center with scar painted over with fluorescent red paint (did not chop out).
- 26" hemlock, rotted stump, S48°E, 16.0' to center, with old scar and red fluorescent paint. Trace of scribe visible.

STATE PARKS CREW SET:

Galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0' NW of iron pipe.

WITNESSED BY:

- R. Hemmer
- S. Doak

C S1/16 SECTION 5

ESTABLISHMENT:

- Set 5/8"x30" iron rod with aluminum cap marked "OREGON STATE PARKS."
- Set galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0' west of the iron rod.
- No BT's available. Corner falls in a logged off area. A cutting line of timber is approximately 100' west.

WITNESSED BY:

- R. Hemmer
- L. Boge
- L. Hetteema

CENTER-QUARTER CORNER SECTION 5

ESTABLISHMENT:

- Set 5/8"x30" iron rod with aluminum cap marked "OREGON STATE PARKS" in a root of a hemlock 1.0' above ground level.
- Set galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 3.0' SW of iron rod.
- 30" hemlock N5°E, 4.8' to center, scribed "C1/4 BT RS691."
- 21" hemlock S60°E, 28.8' to center, scribed "C1/4 BT."
- Placed yellow Parks corner tags on both BT's.

An old logging road is approximately 370' south of corner.

WITNESSED BY:

- R. Hemmer
- L. Boge
- L. Hetteema