

Oswald West Survey
NE¼ Section 1, T3N, R11W, W.M.
Sections 5 & 6, T3N, R10W, W.M.
Tillamook County
December 22, 1981
Page 12

Set steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 1.0' SW of iron rod.

15" hemlock S19°E, 25.5' to center, scribed "T3N R10W E1/16 S6BT."
Center of blaze is 5.0' above ground as blow downs are located all around the base of BT.
7" hemlock S58°W, 15.0' to center, scribed "T3N R10W E1/16 S6BT RS691."

Corner falls 28' S45°W of an old logging road.

WITNESSED BY:

A. Slack
R. Hemmer
L. Boge
L. Hettema

W 1/16 CORNER SECTION 6 (ONLY)

ESTABLISHMENT:

Set 5/8"x30" iron rod with aluminum cap marked "OREGON STATE PARKS."
Set galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0' NE of iron rod.

14" hemlock S20°W, 11.8' to center, scribed "T3N R10W W1/16 S6BT" and attached yellow Parks corner tag.
39" hemlock S55°E, 19.0' to center, scribed "T3N R10W W1/16 S6BT RS691."

Found a squared-off limb 13.0' S55°E from our corner. No scribes on limb.

WITNESSED BY:

R. Hemmer
L. Boge
L. Hettema

NW 1/16 CORNER SECTION 6

ESTABLISHMENT:

Set 5/8"x30" iron rod with aluminum cap marked "OREGON STATE PARKS."
Set galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 1.3' east of iron rod.

13" spruce N80°E, 6.3' to center, scribed "NW1/16BT" and attached yellow Parks corner tag.
14" spruce N30°W, 12.6' to center, scribed "NW1/16BT RS691."

WITNESSED BY:

R. Hemmer
M. Swan
C. Middleton
D. Brumbaugh

C-S-NW 1/64 CORNER SECTION 6

ESTABLISHMENT:

Set 5/8"x30" iron rod with aluminum cap marked "OREGON STATE PARKS."
Set galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0' east of iron rod.