

Oswald West Survey  
NE $\frac{1}{4}$  Section 1, T3N, R11W, W.M.  
Sections 5 & 6, T3N, R10W, W.M.  
Tillamook County  
December 22, 1981  
Page 5

10" hemlock bears N34°E, 30 links, marked "T3N R10W S4BT" (now a 30" stump).  
8" hemlock bears S65°E, 31 links, marked "T3N R10W S9BT" (now a 22" stump).  
7" hemlock bears S20°W, 17 links, marked "T3N R10W S8BT" (now gone).  
6" hemlock bears N38°W, 29 links, marked "T3N R10W S5BT" (now gone).

STATE PARKS CREW FOUND:

A brass cap in the center of a 30" hemlock stump.  
30" hemlock stump, 2.5' high, N39°E, 19.7' to center.  
22" hemlock, 2.5' high, S65°E, 21.4' to center.  
5" hemlock S43°W, 12.7' to center, marked "T3N R10W S8BT."  
7" spruce N60°W, 55.8' to center on slope, marked "T3N R10W S9BT RS707."  
3"x3" square post 4' high, N43°E, 11.2'.  
4"x4"x4" high white post 2.0' southeast of brass cap, with a corner tag by  
ORE. STATE DEPT OF FORESTRY, dated 5/25/76.

WITNESSED BY:

Lee Doss  
R. DePuy  
C. Middleton

$\frac{1}{4}$  CORNER BETWEEN SECTIONS 5 AND 4

ORIGINAL:

Set a post 3' long, 3" square, 24" in the ground for  $\frac{1}{4}$  section corner, marked " $\frac{1}{4}$ S" on west face from which a:

7" hemlock bears N17°W, 5 links, marked " $\frac{1}{4}$ SBT."  
20" hemlock bears N76°E, 46 links, marked " $\frac{1}{4}$ SBT."

STATE PARKS CREW FOUND:

1" iron pipe.  
21" hemlock N78°E, 31.7' to center.  
Downed stump approximately N35°W, 5' distant.

The 1" iron pipe was set by an unknown party but had evidently been there a long time. The two stumps fit very closely for original bearing trees, but they are too badly deteriorated to find any scribe. We believe this corner could very easily be a perpetuation of the original.

STATE PARKS CREW SET:

6" spruce N82°E, 6.8' to center, scribed " $\frac{1}{4}$ S4BT RS691" and attached yellow Parks corner tag.  
8" spruce N42°W, 17.6' to center, scribed " $\frac{1}{4}$ S5BT."  
Set galvanized steel post with plain white paddle 2.0' east of iron pipe.

WITNESSED BY:

R. Hemmer  
L. Doss  
L. Boge  
R. DePuy  
C. Middleton  
M. Swan  
S. Doak

$\frac{1}{4}$  CORNER BETWEEN SECTIONS 6 AND 5

ORIGINAL:

Set a post 3' long, 3" square, 24" in ground for  $\frac{1}{4}$  section corner, marked " $\frac{1}{4}$ S" on west face from which a: