

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 22 and 27, T3N, R8W, W.M.,
Tillamook County, Oregon.

ORIGINAL By Henry Meldrum, October 17, 1891.

14"x11"x6" basalt stone 11" in ground with 1/4 on north face; buried
next to pipe.

36" Hemlock bears S10°E 36 lks.; now remains of badly rotted
root crown, in place.

4" Fir bears N30 3/4°E 13 lks.; now a 38" stump with axe work
visible on burnt out face.

RESTORATION by Louis W. Amort RE2311, April 7, 1952 (Book 2, page
144, Tillamook County Records).

1 1/2"x36" Galvanized iron pipe with 3" bronze cap, 35" in ground;
in mound of rock; in place.

41" Fir stump bears S50 1/2°E 30.0 ft.; now a 41" badly rotted
stump with portions of scribes 1/4 S27 BT 2311 visible.

23" Fir stub bears N56°W 6.6 ft.; now a 23" badly rotted stump
with scribes 1/4 S22 BT visible. Cruisers mark by Richard
Morris above face.

REWITNESSED March 18, 1988

Var. 21 1/2°E

From above pipe with marks "1988 LS1998" added and from which a:

16" Fir bears S63°W 14.1 ft. to face; scribed 1/4S27BT.

17" Fir bears S66°E 23.4 ft. to face; scribed 1/4S27BT.


10" Fir Bears N25°E 23.4 ft. to face; scribed 1/4S22BT.

Metal location poster on new BTs.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by



Anthony J. Klosterman

