

TILLAMOOK COUNTY SURVEYORS OFFICE

1/4 corner common to section 13 T.2N.,R.10W.,W.M.
and section 18 T.2N.,R.9W.,W.M.

1/4
T2N|T2N
R10W.R9W
S13|S18
1989

I set a 1 1/2" iron pipe with a 3" Tillamook county brass cap in a 10" concrete cylinder at the position of a found 2" iron pipe with plug and tack reported on Tillamook County Surveyors map #C-387. This corner is also the Initial Point of Foley Creek no. 3 subdivision.

History of found Monument

I found this monument to be as reported in Tillamook County Surveyors re-witness book 2 at page 188 and on map #C-387 and the accessories found and/or set at that time to now be as follows:

1 1/2" alder N.20*W. 16.6'; (Now 18" alder leaning severely N.23*W. 15.92' to a nail with C.S. brass washer facing the corner).*

8" spruce S.27*E. 9.7'; (Now uprooted stump).

Surveys and re-witnesses of reference;

G.L.O. 2N10 page 15 1873. (no original evidence found)
A-2644, Gene Leuthold L.S. 475 1974.
B-676, Gene Leuthold L.S. 475 1974.
C-387, Allen & Leuthold Plat of Foley Creek No.3 1978.
B-565, O.S.B.F. L.S. 707 1968.
Book 2 Page 188, W.A. Markham R.E.1842.
F-26-16 relocated Miami-Foley county road 1972.
B-751 Robert Olsen L.S. 701 1977
A-1853 John L. Carlich L.S. 287 1969

New Accessories

18" Spruce S.40*E. 12.55' scribed 1/4S18B.TCS distance measured to a nail with a C.S. brass washer in the face.*

84" hat section post West 2.57'.*

*indicates yellow metal Tillamook county corner tag affixed.

Monument Location

This corner is located approximately 2' East of a North-South fence line on the West side of a clearing.

In the presence of Dan McNutt & Al Dvorak

June 1989

Title Allen E. Dussan, C.S.

