

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A decayed fir snag, size indeterminate, bears
S. 45° E., 156 lks. dist., with scribe marks
BT visible on open blaze.

and the remains of bearing trees mkd. by Whitmore

A fir, 18 ins. diam., bears N. 52° E., 39½ lks.
dist., with healed blaze.

A fir, 22 ins. diam., bears S. 36½° E., 10½ lks.
dist., with healed blaze.

A fir, 22 ins. diam., bears S. 75° W., 41 lks.
dist., with healed blaze.

An alder snag, 12 ins. diam., bears N. 45° W.,
9 lks. dist., with scribe marks T3S R10W S27 BT
visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 3 S R 10 W	
S 27	S 26
S 34	S 35
1978	

from which a new bearing tree

A fir, 21 ins. diam., bears N. 74° W., 53 lks.
dist., mkd. T3S R10W S27 BT.

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 22, 23, 26, and 27, perpetuated and
recorded by Mervin Whitmore, Deputy County Surveyor, in
1952, monumented with a wood post, 4 ins. square, 30 ins.
long, projecting 8 ins. above ground, from which the
remains of the original bearing trees:

A fir snag, size indeterminate, bears S. 20° W.,
34 lks. dist., with fragmentary scribe marks
visible on open blaze.

and bearing trees mkd. by Whitmore

A fir, 13 ins. diam., bears N. 44° E., 25½ lks.
dist., with healed blaze.

A fir, 32 ins. diam., bears S. 61° E., 24 lks.
dist., with healed blaze.

A fir, 26 ins. diam., bears S. 32½° W., 28 lks.
dist., with healed blaze.

A fir, 14 ins. diam., bears N. 26½° W., 16 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.