

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

Subdivisions, T. 3 S., R. 10 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by William P. Wright,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, perpetuated and re-
corded by Leonard Whitmore, Deputy County Surveyor, in
1962, monumented with an iron pipe, 1 in. diam., firmly
set, projecting 8 ins. above ground, from which the
remains of the original bearing trees:

A decayed hemlock snag, size indeterminate, bears
N. 75° E., 15 lks. dist., with scribe mark S
visible on open blaze.

and the remains of bearing trees mkd. by Whitmore

A sawed fir stump, 38 ins. diam., bears S. 22° E.,
52 lks. dist., with healed blaze.

A sawed fir stump, 33 ins. diam., bears N. 31° W.,
52 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 3 S R 10 W

$\frac{1}{4}$
S 26 | S 25
1978

from which a new bearing tree

A fir, 4 ins. diam., bears N. 37° W., 6 lks.
dist., mkd. X BT.

Reset iron pipe and set a 5 ft. steel fence post
alongside iron post.

The cor. of secs. 23, 24, 25, and 26, perpetuated and
recorded by Leonard Whitmore, Deputy County Surveyor,
in 1963, determined from the remains of the original
bearing trees:

A root hole, bears N. 40° E., 25 lks. dist., with
a down hemlock alongside, 25 ins. diam., with
healed blaze.

A hemlock stump, 14 ins. diam., bears S. 14° W.,
11 lks. dist., with scribe mark S visible on
opened blaze. (Record, S. 19° W.)

A hemlock stump, 18 ins. diam., bears N. 55° W.,
20 lks. dist., with scribe mark S visible on
open blaze. (Record, N. 66° W.)

and the remains of bearing trees mkd. by Whitmore

A sawed hemlock stump, 30 ins. diam., bears
N. 75° E., 64 lks. dist., with scribe marks
3S R10 S24 BT visible on open blaze.