

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 17 ins. diam., bears S. 18° E., 9½ lks. dist., with scribe marks S22 BT visible on open double blaze.

A fir, 16 ins. diam., bears S. 75° W., 33 lks. dist., with healed double blaze.

A fir, 13 ins. diam., bears N. 16° W., 22½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 9 W	
S 16	S 15
S 21	S 22
1978	

from which a new bearing tree

A fir, 16 ins. diam., bears S. 38½° E., 43 lks. dist., mkd. T4S R9W S22 BT.

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1961, monumented with the original basalt stone, 20 x 18 x 8 ins., firmly set, 15 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, mkd. with 3 grooves on E. and 4 grooves on S. faces, from which the remains of the original bearing trees:

A sawed alder stump, 17 ins. diam., bears S. 83° 20' W., 224 lks. dist., with scribe mark B visible on opened blaze.

and bearing trees mkd. by Whitmore

A fir, 25 ins. diam., bears N. 58° E., 32½ lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 5° E., 33 lks. dist., with healed blaze.

A fir snag, 21 ins. diam., bears S. 56° W., 46 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears N. 26° W., 84 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 9 W	
S 9	S 10
S 16	S 15
1978	

from which a new bearing tree