

T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 6 south, range 10 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 21° E.

East Boundary, T. 6 S., R. 10 W.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Samuel G. Caudle,
U. S. Deputy Surveyor, in 1880)

The $\frac{1}{2}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron pipe, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 20 ins. above ground, from which the remains of the original bearing trees:

A root hole, bears S. 65° E., 69 lks. dist., with a down and decayed hemlock alongside, 20 ins. diam., with scribe marks $\frac{1}{2}$ S BT visible on opened blaze.

A decayed hemlock stump, 30 ins. diam., bears S. 41° W., 16 lks. dist., no marks visible.
(Record, S. 45° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S
R 10 W R 9 W
 $\frac{1}{2}$
S 13 | S 18
1979

from which new bearing trees

A hemlock, 15 ins. diam., bears N. 76° E., 68 lks. dist., mkd. $\frac{1}{2}$ S18 BT.

A hemlock, 24 ins. diam., bears N. 40 $\frac{1}{2}$ ° W., 31 lks. dist., mkd. $\frac{1}{2}$ S13 BT.

Reset iron pipe alongside iron post.

Subdivisions, T. 6 S., R. 10 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by Albert P. Wilson,
U. S. Deputy Surveyor, in 1890)

143

BOOK 6