

County Surveyor's Record, Tillamook County, Oregon

CHAINS

RESTORED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

One Quarter corner common to Sections 1 and 36, T1&2N, R7W, Tillamook County, Oregon.

ORIGINAL

Basalt stone 16" x 7" x 6" now missing, from which a:

4" Maple bears N30°E 22 lks.; now missing.

5" Maple bears S17°E 32 lks.; now missing.

REWITNESSED by W. E. Anderson, County Surveyor, March 22, 1932. (Recorded in Book 69, Page 78, Tillamook County Surveyors Office.)

From above stone from which a:

18" Fir bears N13°E 25.5 ft.; J. E. Scott in March, 1943, re-scribed as Anderson scribing was burned out.

60" Fir bears N67°E 37.7 ft.; J. E. Scott in March, 1943, found 60" stump cut just above bottom of face. Re-scribed below old face.

Stake, now missing.

RESTORATION by J. E. Scott, RE 294, March, 1943 (Recorded in Book 1, Page 169, Tillamook County Surveyors Office).

Set 1½" x 54" pipe with brass cap, now missing, from which a:

(Anderson's) 18" Fir bears N13°E 25.5 ft.; now scribes BT visible.

(Anderson's) 60" Fir bears N67°E 37.7 ft.; now portions of 1/4 BT CS remaining.

4" x 4" x 60" Cedar guard post; found out of place, two sides burned, portions of scribes PROP COR and R7W remain on other two sides.

RESTORED

Var. 21½°E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T2N R7W ¼ S36 S1 T1N 1982 RS 1662" 30 inches in ground, in mound of rock, from which a:

11" Fir bears N56°E 19.3 ft. to face; scribed ¼ S36 BT.

7" Fir bears S24°W 4.7 ft. to face; scribed ¼ S1 BT.


Set 4" x 4" x 60 white painted Cedar post 1.5 ft. SE of corner pipe. Oregon State Forestry Department metal location poster on 7" Fir BT.

Dated February 23, 1982.

Restored by David B. Buchholz under my direction.
David B. Buchholz, Transitman



Loren R. Steele



Present and witnessed by Danny J. Benson