

RESTORED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

Standard one quarter corner for Section 36, T1N, R8W, W.M.,
Tillamook County, Oregon.

ORIGINAL By Samuel D. Snowden, September 15, 1856.

Post; missing.

24" Alder bears NORTH 46 lks.; missing.
3" Ash bears N55°W 13 lks.; missing.

RESTORATION by Henry Meldrum, August 9, 1884.

10"x10"x8" basalt stone marked BL with 1/4 on North face; found
in place with poor chisel marks visible.

24" Alder bears S10°W 16 lks.; found some rotted wood and root
holes in place.
12" Alder bears N61°W 42 lks.; missing.

REESTABLISHED by A.V. Benedict, RE1960, 1942 (Book 1, page 14 and 170,
and plat #F-28-2 Tillamook County Records). Corner location was
incorrectly proportioned and pipe set in erroneous position.

1 1/2" iron pipe, in mound of rock; in place, flush with ground,
bears N22 1/2°W 47.2 ft. from stone.

RESTORED

Set 1 1/2"x30" Aluminum pipe with 3 3/4" cap marked "STATE OF
OREGON DEPARTMENT OF FORESTRY SC T1N R8W 1/4 S36 1987 LS1998",
26" in ground, in mound of rock, placed original stone on North
side of pipe, and from which a:

Var 21 1/2°E

14" Fir bears N14°W 53.3 ft. to face; scribed 1/4S36SCBT.
11" Hemlock bears N23°E 38.4 ft. to face; scribed 1/4S36SCBT.

Metal location poster on new BTs.



Also brass washers marked "LS1998" on new BTs.

4"x4"x72" white painted Cedar post bears N59°E 3.5 ft. from pipe.

Dated June 23, 1987.

Restored by David B. Buchholz under my direction.
David B. Buchholz, Survey Crew Chief

Present and witnessed by Clifford R. Foster



BOOK 6