

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 3 and 34, T2&3S, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Albert P. Wilson, June 17, 1891.

Post; missing, from which a:

26" Hemlock bears N34 1/2°E 35 lks; now a badly rotted windfall,
no scribes visible.

13" Hemlock bears N56 1/2°W 48 lks; now a 11" badly rotted stub,
axe work visible on burnt out face.

RESTORATION by Louis W. Amort RE2311, August 15, 1952, (Book 2,
Page 205, Tillamook Co. Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30 inches in
ground; found in place, from which a:

40" Fir snag bears N43°E 22.9 ft.; now a 40"x30 ft. high rotted
snag with faint scribe marks 1/4 S34 BT RE2311 visible.

40" Fir snag bears S83°E 58.3 ft.; now a 40"x20 ft. high rotted
snag with faint scribe marks 1/4 S3 BT RE2311 visible.

REWITNESSED

Var. 21 1/2°E

From above pipe, added marks "1987 LS1998" and from which a:

28" Fir bears S38°E 33.4 ft. to face; scribed 1/4S3BT.


14" Fir bears N21°E 43.8 ft. to face; scribed 1/4S34BT.

Metal location poster on new BTs.


Also brass washers marked "LS1998" on new BTs.

Dated June 25, 1987.

Rewitnessed by



Anthony J. Klosterman



Present and witnessed by David B. Buchholz
Clifford R. Foster

BOOK 6

829