

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

Section corner common to Sections 4, 5, 8 and 9, T2N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL By Henry Meldrum, July 31, 1893.

14"x11"x7" basalt stone; missing.

- 40" Fir bears N21°E 78 lks.; now a 48" stump, face cut off when logged. Axe work visible on bottom of face.
- 19" Hemlock bears S48°E 39 lks.; now root crown, in place.
- 10" Hemlock bears S14°W 61 lks.; now a 15" down snag with portions of scribes visible.
- 16" Hemlock bears N24°W 53 lks.; now a 20" badly rotted stump, face rotted off.

RESTORATION by Louis W. Amort, RE2311, August 15, 1952 (Book 2, page 171, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 28" in ground; in place.

- 5" Hemlock bears S42 1/2°W 86.3 ft.; now 18", face closed.
- 3" Hemlock bears S37 1/2°E 20.5 ft.; now a 5", uproot, exposed scribes S9.
- 54" Fir stump bears N31 1/2°E 60.3 ft.; now 54", with scribes T2N R7W S4 B visible.
- 48" Fir stump bears N56°W 60.0 ft.; now 48" with portions of scribes visible on rotted face.

REWITNESSED August 6, 1987

Var 21 1/2°E

From above pipe with marks "1987 LS1998" added, and from which a:


- 9" Hemlock bears N69°E 7.9 ft. to face; scribed T2NR7WS4BT.
- 10" Hemlock bears N58°W 13.4 ft. to face; scribed T2NR7WS5BT.
- 11" Hemlock bears S72°W 14.8 ft. to face; scribed T2NR7WS8BT.
- 9" Hemlock bears S29°E 15.2 ft. to face; scribed T2NR7WS9BT.

Metal location poster on new BTs.


3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed be David B. Buchholz and Clifford. R Foster.

Rewitnessed by



Anthony J. Klosterman



BOOK 6

333