

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 24 and 25, T1N, R10W, W.M., Tillamook County, Oregon.

NO EVIDENCE OF ORIGINAL CORNER FOUND.

REESTABLISHED by Richard A. Morris LS401, December 31, 1959 (Book 2, page 436, also Plat #B-419, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 33" in ground, in mound of stone; in place, mound of stone missing.

30" Fir bears N27 1/2E 19.1 ft.; now a 30" badly rotted stump with face rotted out.

23" Fir bears S86E 15.0 ft.; now a 26" badly rotted stump with scribes 1/4 S25 BT visible.

4"x4"x60" white painted Cedar post 1.0 ft. NE of pipe; in place

REWITNESSED August 30, 1988

Var. 21 1/2 E

From the above pipe with marks "LS1998 1988" added, and from which a:

15" Hemlock bears N61W 6.4 ft. to face; scribed 1/4S24BT.

12" Fir bears S07E 38.2 ft. to face; scribed 1/4S25BT.


Metal location poster on new BTs.

Also metal location poster on 23" Fir BT S86E 15.0 ft.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by



*Anthony J. Klosterman*

